



SERIES 20 ROTARY SWITCHES

ELECTROSWITCH		SERIES 20 INSTRUMENT & CONTROL SWITCHES <input type="checkbox"/> 20 K STANDARD <input type="checkbox"/> 20 M PLUG IN MODULE <input type="checkbox"/> 20 P LIGHTED FRONT OF PANEL MOUNT		SWITCH NUMBER _____ ENGRAVING CODE _____	REV _____																																																
HANDLES <input type="checkbox"/> Knurled <input type="checkbox"/> Oval <input type="checkbox"/> Pistol-Grip <input type="checkbox"/> None <input type="checkbox"/> Removable in Pos _____	ACTIONS <input type="checkbox"/> Maintained <input type="checkbox"/> Spring return to Vertical (0°) OTHER FEATURES <input type="checkbox"/> Slip contacts <input type="checkbox"/> Pull to lock	Panel Thickness _____ Depth behind panel _____ SPECIAL FEATURES		MOUNTING & LIGHT PACKAGES <input type="checkbox"/> 2-HOLE PANEL MOUNT NO LIGHT PACKAGE <input type="checkbox"/> 4-HOLE PANEL MOUNT 2 LIGHTS <input type="checkbox"/> 4-HOLE PANEL MOUNT 3 LIGHTS LAMPS ARE 24-28 VOLTS <input type="checkbox"/> DROPPING RESISTORS FOR 125VDC SUPPLY <input type="checkbox"/> NO DROPPING RESISTORS LAMP COLORS 1 _____ 2 _____ 3 _____	HANDLE POSITIONS <input type="checkbox"/> 45° <input type="checkbox"/> 90° <input type="checkbox"/> 30° <input type="checkbox"/> TARGET																																																
X-CHART FOR SERIES 20 SWITCHES																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="12" style="text-align: center;">TITLE ENGRAVING</td> </tr> <tr> <td colspan="6" style="text-align: center;">Use for all except slip contacts</td> <td colspan="6" style="text-align: center;">Use for Switches with slip contacts</td> </tr> <tr> <td colspan="6" style="text-align: center;">POSITION ENGRAVING</td> <td colspan="6" style="text-align: center;">FOR 20K & 20P ONLY</td> </tr> <tr> <td colspan="6"></td> <td colspan="6"></td> </tr> </table>						TITLE ENGRAVING												Use for all except slip contacts						Use for Switches with slip contacts						POSITION ENGRAVING						FOR 20K & 20P ONLY																	
TITLE ENGRAVING																																																					
Use for all except slip contacts						Use for Switches with slip contacts																																															
POSITION ENGRAVING						FOR 20K & 20P ONLY																																															
DECK	CONTACTS HANDLE END	POSITIONS								3 from																																											
		1	2	3	4	5	6	7	8	1	2	2	4	4																																							
1	10-1-1-02 30-1-1-04																																																				
2	50-1-1-06 70-1-1-08																																																				
3	90-1-1-10 110-1-1-12																																																				
4	130-1-1-14 150-1-1-16																																																				
5	170-1-1-18 190-1-1-20																																																				
6	210-1-1-22 230-1-1-24																																																				
7	250-1-1-26 270-1-1-28																																																				
8	290-1-1-30 310-1-1-32																																																				
9	330-1-1-34 350-1-1-36																																																				
10	370-1-1-38 390-1-1-40																																																				
11	410-1-1-42 430-1-1-44																																																				
12	450-1-1-46 470-1-1-48																																																				

										------------------------------	----	----	----	------------------------	----	----	----		JUMPERS FOR SERIES 20K & 20P				JUMPERS FOR SERIES 20M					4	3	1	2	4	3	1	2		8	7	5	6	8	7	5	6		12	11	9	10	12	11	9	10		16	15	13	14	16	15	13	14		20	19	17	18	20	19	17	18		24	23	21	22	24	23	21	22		28	27	25	26	32	31	29	30		32	31	29	30	36	35	33	34		36	35	33	34	40	39	37	38		40	39	37	38	44	43	41	42		44	43	41	42	48	47	45	46		48	47	45	46										
LAMP WIRING (20M)																																																																																																																																												
SLIP CONTACTS WILL BE GROUPED AT REAR OF SWITCH. A MAXIMUM OF 4 SLIP CONTACTS ARE AVAILABLE.																																																																																																																																												
SHOW JUMPERS TO BE SUPPLIED																																																																																																																																												
								----------------------------------	--	--	--	--	--		DOCUMENT CONTROL							Quality Assurance ANSI/ASME							NQA-1 Qualification ESC-STD-1000							DRAWING MASTER							Switch: 20K, 20P, 20M																																																																																																	
MADE BY:	DATE:	COMPANY		DWG NO.																																																																																																																																								
APPR BY:	DATE:			SHEET	OF																																																																																																																																							