














SELECTOR GUIDE ROTARY SWITCHES

CAM-ACTION POWER SWITCHES

 CHARACTERISTICS	 KW12	 KW16	 KW20	 KW25	 KW32	 KW40	 KW63	 KW100	 KW200	 KW400	 KW600	 KW800
SECTIONS POLES POSITIONS DETENTING ANGLE	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	1-12 1-24 2-12 30, 45, 60, 90	2-12 1-12 2-12 30, 45, 60, 90	3-12 1-8 2-8 30, 45, 60, 90	4-12 1-6 2-6 30, 45, 60, 90
ELECTRICAL RATINGS Continuous Rating Interrupting Current 120VAC 240VAC 600VAC 24VDC	20A-240VAC 12A 12A 12A	25A-600VAC 16A 16A 16A	25A-240VAC 20A 20A 20A	32A-600VAC 25A 25A 25A	40A-600VAC 32A 32A 32A	63A-600VAC 40A 40A 40A	80A-600VAC 63A 63A 63A	125A-600VAC 100A 100A 100A	200A-600VAC 200A 200A 200A	400A-600VAC 400A 400A 400A	600A-600VAC 600A 600A 600A	800A-600VAC 800A 800A 800A
Momentary Current 1 second	275A	550A	407A	690A	725A	914A	2500A	3000A	4400A	4400A	4400A	4400A
Overload Current (50 operations) 240VAC 600VAC	40.8A	91.2A	91.2A	132A 102A	168A 132A	252A 168A	324A 252A	480A 312A	924A 372A	924A 372A	924A 372A	924A 372A
Dielectric Strength Insulation Resistance Contact Resistance	1500VRMS 100 megohms 30 milliohms	2200VRMS 100 megohms 30 milliohms	1500VRMS 100 megohms 30 milliohms	2200VRMS 100 megohms 30 milliohms	2200VRMS 100 megohms 30 milliohms	2200VRMS 100 megohms 10 milliohms	2200VRMS 100 megohms 10 milliohms	2200VRMS 100 megohms 5 milliohms	2200VRMS 100 megohms 5 milliohms	2200VRMS 100 megohms 5 milliohms	2200VRMS 100 megohms 5 milliohms	2200VRMS 100 megohms 5 milliohms
HORSEPOWER RATINGS 3-phase ratings - Reduce by 1/2 for 1-phase 220/240VAC 440/480VAC 550/600VAC	2 HP	5 HP 10 HP 10 HP	5 HP	7.5 HP 15 HP 15 HP	10 HP 20 HP 20 HP	15 HP 25 HP 25 HP	20 HP 40 HP 40 HP	30 HP 50 HP 50 HP	60 HP 75 HP 60 HP			
MOUNTINGS Single-Hole 2-Hole 4-Hole Base-mount Waterproof-mount Door-mount	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes
LOCKING FEATURES Key-interlock Padlock	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes
SPECIAL DRIVES Key-operated Ganged Gear-operated Spring Return	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes
APPROVALS U/L Listed CSA Certified	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Listed Yes Yes	Recognized Yes Yes	Recognized Yes Yes	Recognized Yes Yes

See OTHER SIDE for Detent & Snap-action switches