

## **DETENT-ACTION SWITCHES**

ELECTROSWITCH DETENT SWITCH WORKSHEET				
FEATURES:  SERIES HANDLES  21 Oval Flush	ROTARY ACTION:  Maintained Spring-return		movable inPosition (s)	
24	CONTACTS:  Nonshorting Contacts break-before-make  Shorting Contacts make-before-break	Key Operated (Series 31) Key Removable inPosition (s)  Solenoid Lock  Push-to-Turn  Waterproof Mount  Waterproof Mount		
SWITCH POS	ITION TABULATION (FRONT VIEW)		HANDLE POSITIONS	
TITLE ENGRAVING:	POSITION ENGRAVING		* *	
CONTACTS	POSITIONS	☐ 45° SERIES 21, 24, 31	□ 30° □ 22 ½°  SERIES SERIES  25, W-2 28	
CONTACTS HANDLE END 1 2 3 4		13 14 15 16	DECK LAYOUTS	
		8 0 0 2 7 0 0 5	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
		8 0 2 7 6 0 5	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
			$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
		1 1 1 1 1 1	V-2 & W use numerical terminal markings	
		Indicate external	28 use alphabetical terminal markings terminal connectors required	
Switch is viewed from handle end  * Terminal numbers are preliminary pending factory review and approval.				
MADE BY: DATE: APPR DATE:	COMPANY		DWG NO. SHEET OF	